


BITS2POWER® LINE TERMINATOR

Product description

- Bits2Power Line terminator
- 2 wire connection
- 3 Year Warranty
- CE certified
- IP67

Applied Standards

EN55022 EN55024



Technical notes

Dimensions	24,5x21,5mm	
Weight	0,1 kg.	
Housing	ABS	
Color	Black	

Ordering data

Туре	Article number
B2P Line Terminator	90519050

- ① Tolerance of 5%
- Nominal output voltage is # of LEDS x LED forward voltage

 Tolerances of 5% and for each circuit
- Percentage of output current
 To be determined











Electrical Characteristics

Input	48Vdc

Connections

Input voltage	Positive	Orange	AWG20, 150mm
	Negative	Black	AWG20, 150mm



Mechanical Dimensions

Overall dimensions

L = 24,5 x W = Ø21,5 mm

Environmental characteristics

Storage temperature	-20 – +85°C	
Operating temperature	- 5 – +40°C	
Operating humidity	10-95% RH	
IP classification	IP67	

Installation and Safety Information

Installation must be carried out under observation of the relevant regulations and standards. The following advice must be followed:

- Terminator is used at the end of the Bits2Power communication lines.
 See PDC600 controller manual for system installation details.
 The device contains components that are sensitive to electrostatic
- The device contains components that are sensitive to electrostatic discharge and may only be installed in the factory and on site if appropriate EOS/ESD protection measures have been taken.
 For outdoor or damp locations, be aware of the IP classification.
- For outdoor or damp locations, be aware of the IP classification All above specifications must be met in order to qualify for the 3 year warranty.

Packaging

i ackaging		
Plastic bag		
Quantity each Bag	1	
Weight (kg)	0,1	

